



NAVILOCK

Navilock NL-457DL EasyLogger

u-blox5 SuperSense® Chipset

The NL-457DL EasyLogger has an internal web interface, which use Windows Internet Explorer to display your recorded tracks. You can combine images with track marks and upload this to the free of charge Panoramio webpage. It guarantees you have your pictures to your stored tracks, wherever available, where you have a web access and an available USB port.

Forget the days, when you must install software on each PC, to display your data.

Generell Spezifikationen

- u-blox5 SuperSense® GPS Chipset
- Sensitivity: -160 dBm
- Internal web interface to Google® Earth
- Internal patch antenna
- 19 hours life time with on battery pack
- Communication over USB Host
- Password protection
- Powersave Mode
- Adjustable recording mode, auto, bicycle, on foot and hand
- Display for time and distance, course data speed, average speed, memory space and current position
- Memory for 94,000 Waypoints
- Support "Push-to-log"
- Time zone at the NL-457DL adjustable
- Longitude and latitude in 3 different formats representable

Specification

- Chipset: u-blox5 SuperSense®
- Frequency: L1, 1575.42 MHz
- C / A code: 1.023 MHz
- Channels: 50 channels max.
- Sensitivity: -160 dBm
- Accuracy 10m, 2D RMS / 5m, 2D RMS, WAS corrected / 2.5m, DGPS corrected
- Speed: 0.1 m / s
- Time: 1µs tact to GPS time

Date

- Default: WGS-84

Time

- Reacquisition: 0.1 sec. At an average
- Hot start: 3.5 sec. At an average
- Warm: 25 sec. At an average
- Cold start: 30 sec. At an average

Dynamic characteristics

- Reception Altitude: Max 18,000 meters (60.000 feet)
- Reception time: Max 515 meters / second
- Acceleration: 4g Max
- Vibration: Max 20m/sek × 3

Physical properties

- Power: 2 replaceable AAA batteries
- Battery life time: max. about 19 hours
- Dimensions: 85mm x 31mm x 23mm
- Weight: 37g without batteries
- Operating temperature: -10 ° C to +60 ° C

Delivery

- 1x NL-457DL
- 1x lanyard
- 1x Manual

Compatibility

- Windows XP and Vista
- NO LINUX and MAC SUPPORT

The recorded data are compatible to Google Maps, Google Earth, Virtual Earth, GPX, OziExplorer, and PaPaGo TimeMachineX.



Product no. 60119
Country of origin: Taiwan
Customs tariff number.: 85269120

www.navilock.com