

Navilock Power Bank 10200 mAh 2 x USB Type-A female with Qualcomm® Quick Charge™ 3.0

Description

This external battery by Navilock can be used for all common devices with USB power supply. The power bank has two USB Type-A ports to charge two devices at the same time. One USB port offers the Qualcomm® Quick ChargeTM 3.0 support, thus it can charge e.g. smart phones with Qualcomm® Quick ChargeTM 3.0 function in much shorter time. Further the Micro USB port has the Qualcomm® Quick ChargeTM 3.0 support thus the power bank can recharged faster than conventional models.



Item no. 41501

EAN: 4043619415014 Country of origin: China Package: Retail Box

Specification

- Connector:
 - 2 x USB Type-A female
 - 1 x USB Type Micro-B female
- · Capacity: 10200 mAh
- Output:

Port 1: Qualcomm® Quick ChargeTM 3.0 Class A: 3.6 ~ 6.5 V / 3 A, 6.5 ~ 9 V / 2.0 A,

9 ~ 12 V / 1.25 A

Port 2: 5 V / 2.4 A

- Input: Quick ChargeTM 3.0 Class A: $3.6 \sim 6.5 \text{ V} / 3 \text{ A}$, $6.5 \sim 9 \text{ V} / 2.1 \text{ A}$,
 - 9 ~ 12 V / 1.25 A
- On / Off switch
- · LED indicator for battery status
- · LG battery, lithium-ionen
- Overcharge and over-discharge protection
- Input overvoltage protection and output overvoltage protection
- Short circuit protection
- · Overheating protection
- Automatic power-off
- Operating temperature: 0 °C ~ 40 °C



- Storage temperature: -20 °C ~ 80 °C
- Operating humidity: < 75 %
- Storage humidity: < 45 %
- Weight of the power bank: ca. 240 g
- Colour: silver
- Dimensions (LxWxH): ca. 137 x 64 x 22 mm

System requirements

• USB device

Package content

- Power bank
- USB Type-A to Type Micro-B cable, length ca. 15 cm
- Bag
- User manual

Images













General

| LED indicator: | battery status |
|----------------|--|
| Protection: | Overcharge protection Over-discharge protection Output overvoltage protection Input overvoltage protection Short circuit protection Overheating protection Automatic power-off |

Interface

| Output: | 1 x USB Type-A female Qualcomm® Quick Charge TM 3.0 Class A: 3.6 $^{\sim}$ 6.5 V / 3 A, 6.5 $^{\sim}$ 9 V / 2.0 A, 9 $^{\sim}$ 12 V / 1.25 A 1 x USB Type-A female 5 V / 2.4 A |
|---------|---|
| Input: | 1 x USB Type Micro-B female Quick Charge TM 3.0 Class A: 3.6 \sim 6.5 V / 3 A, 6.5 \sim 9 V / 2.1 A, 9 \sim 12 V / 1.25 A |

Technical characteristics

| Storage temperature: | -20 °C ~ 80 °C |
|------------------------|----------------|
| Operating temperature: | 0 °C ~ 40 °C |
| Capacity: | 10200 mAh |

Physical characteristics

| Weight: | 240 g |
|---------|--------|
| Length: | 137 mm |
| Width: | 22 mm |
| Height: | 64 mm |
| Colour: | silver |