

# Navilock NL-65AT MMCX additional GPS antenna

## Description

The NL-65AT is recommended for use in vehicles using thermal protective vitrification. Thereby, the GPS receiver or PNA achieves higher signal strength, and thus a higher number of available satellites. Reception clearly improves by use of the NL-65AT, particularly when the GPS receiver or PNA is mounted in a location where the sky is not visible.



5 m

**Item no. 61232**

EAN: 4043619612321

Country of origin: Taiwan

Package:

## Technical details

- Externally active GPS magnet antenna
- MMCX connector
- Cable length 5.0 m
- RG174 cable with impedance of 50 Ohm
- Watertight at a depth of 0.5 m for 30 minutes
- Current consumption approximately 13 mA at 3 V and 18 mA at 5 V
- Temperature range for use -30 °C to +80 °C
- Temperature range for storage -40 °C to +100 °C
- Dimensions: 40.5 mm x 38.0 mm x 12.3 mm

## Package content

- NL-65AT MMCX additional GPS antenna

## Images



## Herstellerinformation

---

Strasse	Beeskowdamm 13/15
PLZ	14167
Ort	Berlin
Land	Deutschland
E-Mail	<a href="mailto:info@navilock.de">info@navilock.de</a>
Webseite	<a href="http://www.navilock.de">www.navilock.de</a>