

Navilock NL-302U USB GPS Receiver

Description

The USB GPS receiver based on SiRFstarIII™ chipset has a built-in antenna for high sensitivity.

You can use this GPS Receiver with a Notebook and a suitable routing software for navigation.



Item no. 61422

EAN: 4043619614226

Country of origin: Taiwan,
Republic of China

Package: Retail Box

Special features

Please note that the SiRFstarIII chipset used here has reached the end of its production cycle. This receiver is delisted in the next few weeks.

Specification

- SiRFstarIII™ high performance and low power chipset
- Accepts the signals of up to 20 satellites at the same time
- Supports NMEA 0183 protocols: GGA, GSA, GSV, RMC, GLL, VTG
- USB specification 1.1
- 4800 Baud
- IPX6 protection class
- Magnetic, non-slip on the bottom
- LED-indicator for GPS-status
- Cold start in about 42 sec.
- Warm start in about 38 sec.
- Hot start in about 1 sec.
- Dimension (LxWxH): 65 mm x 45 mm x 22 mm
- Cable lenght: 1.50 m

System requirements

- Windows 98/ME/2000/XP/Vista/7/8, Linux ex Kernel 2.6, Mac OS 8, 9, 10x
- PC or Notebook with a free USB Port

Package content

- USB GPS Receiver
- Driver CD
- User manual

Images

