

Navilock NL-8008T Stereo Jack TRRS LVTTTL Multi GNSS Receiver u-blox 8 1.5 m

Description

The 4 pin stereo jack LVTTTL multi GNSS Receiver based on u-blox 8 chipset has a built-in antenna for high sensitivity.



Item no. 62586

EAN: 4043619625864

Country of origin: Taiwan,
Republic of China

Package: Retail Box

Technical details

Images



General

Protection class:	IPX6
Suitable for indoor:	yes
Suitable for outdoor:	yes

Interface

Connector:	1 x 3.5 mm 4 pin audio stereo jack male
------------	---

Technical characteristics

Operating voltage:	5 V DC
Chipset:	u-blox M8030-KT
Frequency range:	BEIDOU: B1, 1561.0980 MHz GPS 1575.42 MHz QZSS L1, 1575.4200 MHz GALILEO: E1 1575.4200 MHz GLONASS: L1, 1602 (k x 0.5625) MHz
Operating temperature:	-20 °C ~ 60 °C
Current consumption:	45 mA
Sensitivity:	-167 dBm
Update rate:	up to 18 Hz

Physical characteristics

Housing colour:	black
Housing material:	PC / ABS
Cable length incl. connectors:	1.5 m
Length:	65 mm
Width:	45 mm
Height:	22 mm

Manufacturer information

Street	Beeskowdamm 13/15
Postal code	14167
City	Berlin
Country	Deutschland
E-Mail	info@navilock.de
Website	www.navilock.de