

# Navilock Connection Cable MD6 female serial > 3,5 mm 4 pin stereo jack male 90° TTL (5 V) 52 cm

## Description

The connection cable by Navilock converts the serial signals for all MD6 receivers to TTL 5 V signals. Compatible with TTL/CMOS is this interface suitable for GPIO, UART, Controller and CPU.



ca. 52 cm

**Item no. 62880**

EAN: 4043619628803

Country of origin: Taiwan,  
Republic of China

Package: Zip poly bag

## Specification

- Connectors:
  - 1 x MD6 female >
  - 1 x 3.5 mm 4 pin stereo jack male 90°
- Chipset: ASIX ZT3221LEEY
- Data transfer: bidirectional
- Cable gauge: 28 AWG
- Voltage: 5 V
- Cable colour: black
- Length incl. connectors (L): ca. 52 cm

## System requirements

- A Navilock serial MD6 GNSS receiver

## Package content

- Connection cable for GNSS receiver
- Navilock support CD

## Images



## General

Style:	angled 90°
--------	------------

## Interface

connector:	1 x MD6 jack
Connector 1:	1 x 3.5 mm 4 pin audio stereo jack male

## Technical characteristics

Chipset:	ASIX ZT3221LEEY
Voltage:	5 V

## Physical characteristics

Cable colour:	black
Cable length incl. connector:	52 cm