
Navilock Connection Cable MD6 female serial > 5 x 1 pin pin header, pitch 2.54 mm TTL (5 V) 52 cm

Description

The connection cable by Navilock converts the serial signals for all MD6 receivers to TTL 5 V signals. Compatible with TTL/CMOS this I/O interface is suitable for GPIO, UART, controller and CPU.



ca. 52 cm

Item no. 62883

EAN: 4043619628834

Country of origin: Taiwan, Republic of China

Package: Zip poly bag

Specification

- Connectors:
  1 x MD6 female >
  5 x 1 pin female pin header
- Pitch: 2.54 mm
- Chipset: ASIX ZT3221LEEY
- Data transfer: bidirectional
- Cable gauge: 28 AWG
- Voltage: 5 V
- Cable colour: black
- Length incl. connectors (L): ca. 52 cm

System requirements

- A Navilock serial MD6 GNSS receiver


© 2024 by Navilock. All names and symbols mentioned here are property of the respective producer.
Printing errors, changes and errors excepted.

Package content

• Connection cable for GNSS receiver
• Navilock support CD

Images





© 2024 by Navilock. All names and symbols mentioned here are property of the respective producer.
Printing errors, changes and errors excepted.

Interface

connector:	1 x MD6 jack
Connector 1:	1 x 2,54 mm pin header 5 pin female

Technical characteristics

Chipset:	ASIX ZT3221LEEY
Voltage:	5 V

Physical characteristics

Cable colour:	black
Cable length incl. connector:	52 cm

© 2024 by Navilock. All names and symbols mentioned here are property of the respective producer.
Printing errors, changes and errors excepted.