

Navilock Connection Cable MD6 female serial > 3.5 mm 4 pin stereo jack male 90° LVTTL (3,3 V) 52 cm

Description

The connection cable by Navilock converts the serial signals for all MD6 receivers to LVTTL 3,3 V signals. Compatible with LVTTL/CMOS is this interface suitable for GPIO, UART, Controller and CPU.



ca. 52 cm

Specification

- Connectors:
1 x MD6 female >
1 x 3.5 mm 4 pin stereo jack male 90°
- Chipset: ASIX ZT3221LEEY
- Data transfer: bidirectional
- Cable gauge: 28 AWG
- Voltage: 3.3 V
- Cable colour: black
- Length incl. connectors (L): ca. 52 cm

System requirements

- A Navilock serial MD6 GNSS receiver

Package content


- Connection cable for GNSS receiver
- Navilock support CD

Item no. 62926

EAN: 4043619629268

Country of origin: Taiwan, Republic of China

Package: Zip poly bag



Images



General	
Style:	angled 90°
Interface	
connector:	1 x MD6 jack
Connector 1:	1 x 3.5 mm 3 pin stereo jack male
Technical characteristics	
Chipset:	ASIX ZT3221LEEY
Voltage:	3.3 V
Physical characteristics	
Cable colour:	black
Cable length incl. connector:	52 cm