



Navilock Connection Cable M8 female serial waterproof > 5 x open wire LVTTTL (3.3 V) 1.2 m

Description

The waterproof connection cable by Navilock converts the serial signals for all M8 receivers to LVTTTL 3.3 V signals. Compatible with LVTTTL/CMOS 3.3 V is this interface suitable for GPIO, UART, Controller and CPU.



ca. 1,2 m

Item no. 62938

EAN: 4043619629381

Country of origin: Taiwan, Republic of China

Package: Zip poly bag

Specification

- Connectors:
 - 1 x M8 female >
 - 1 x 5 pin open wire
- Chipset: ASIX ZT3221LEYY
- Data transfer: bidirectional
- Cable gauge: 28 AWG
- Voltage: 3.3 V
- Waterproof
- Cable colour: black
- Length incl. connectors (L): ca. 1.2 m


System requirements

- A Navilock serial M8 GNSS receiver

Package content

- Connection cable for M8 GNSS receiver
- Navilock support CD

Images



General

Protection category:	waterproof
----------------------	------------

Interface

connector:	1 x M8 female
Connector 1:	1 x open wire

Technical characteristics

Chipset:	ASIX ZT3221LEEY
Voltage:	3.3 V

Physical characteristics

Cable colour:	black
Cable length incl. connector:	1.20 m