Delock Wireless Display USB Type-C™ Adapter Full HD - HDMI + VGA with Card Reader and Hub

Description

This adapter by Delock can be used to **wirelessly** transmit an audio and video signal in **1080p** format **over a range of up to 10 m** . Only the transmitter has to be connected to the USB Type-C™ port of the device and the receiver via **HDMI or VGA** cable to a TV, projector or similar. **Both video outputs can be used at the same time** to display the signal on two displays at the same time.

Integrated card reader and hub
Two built-in USB Type-A ports allow the use of peripherals, an **SD** and a **Micro SD** slot allow the use of memory cards.

Easy transport
For transport, the transmitter unit can easily be inserted into the receiver unit's deepening, where both parts are held together by a magnet.

Plug & Play
After connecting the two parts of the device, the connection is automatically established, no drivers need to be installed or settings made.

Item no. 87775

EAN: 4043619877751
Country of origin: China
Package: Retail Box

Technical details

- Connectors:
  Transmitter:
  1 x USB Type-C™ male
  2 x SuperSpeed USB (USB 3.2 Gen 1) Type-A female
  1 x SD slot
  1 x Micro SD slot
  Receiver:
  1 x HDMI-A female
  1 x VGA female
  1 x 3.5 mm 3 pin stereo jack female
  1 x USB Type-C™ female (power supply)

- Resolution:
  HDMI up to 1920 x 1080 @ 60 Hz
  VGA up to 1920 x 1080 @ 60 Hz
  (depending on the system and the connected hardware)
- Transmission of audio and video signals
- Functions: Mirrored or Extended; only one monitor can be extended,
  all others are mirrored
- Bandwidth: 5 GHz, operating range up to 10 m
- It can be used two memory cards at the same time
- Colour: black
- Cable length: ca. 15 cm
- Dimensions transmitter (LxWxH): ca. 111 x 56 x 13 mm
- Dimensions receiver (LxWxH): ca. 115 x 61 x 22 mm

System requirements

- Android 10.0 or above
- iPad Pro (2018)
- Linux Kernel 5.4 or above
- Mac OS 10.15.6 or above
- Surface Pro 7
- Windows 8.1/8.1-64/10/10-64
- Device with a free USB Type-C™ port and DisplayPort alternate mode or with a free
  Thunderbolt™ 3 port
- A free USB Type-A female port (power supply)

Package content

- Transmitter
- Receiver
- USB power cable, length: ca. 0.8 m
- User manual

Images

© 2024 by Navilock. All names and symbols mentioned here are property of the respective producer.
Printing errors, changes and errors excepted.

www.navilock.com
87775

3 / 4
31.05.2022

General

Supported operating system:	Linux Kernel 5.4 or above Mac OS 10.15.6 or above Surface Pro 7 Windows 10 32-Bit Windows 10 64-Bit Windows 8.1 32-Bit Windows 8.1 64-Bit iPad Pro (2018) Android 10.0 or above

Interface

Output:	1 x 3.5 mm 3 pin stereo jack female 1 x SD slot 1 x Micro SD Slot 1 x HDMI-A female 1 x VGA female 2 x USB 5 Gbps Type-A female
Input:	1 x USB Type-C™ female (power supply) 1 x USB Type-C™ male

Technical characteristics

Maximum screen resolution:	1920 x 1080 @ 60 Hz

Physical characteristics

Housing material:	Plastic
Cable length:	15 cm
Colour:	black